

OMEGA POWER SYSTEM

For us, it's not just business. It's personal.

Compressor Model: **KELVIN CSA 22-08 575** --

GENERAL DATA				
Nominal Input Power	kW	22		
	HP	30,0		
Drive Type	-	Belt		
Entire Compressor IP Grade	-	IP 20		
Working Pressure	bar	8		
	psi	116		
Min. Working Pressure	bar	6,5		
	psi	94		
Ambient Working Temperature	°C	min. +2	-	max. +45
Main Voltage Supply value	V - ph	575 ±10%	-	n.ph 3~
Auxiliary Voltage Supply value	V - ph	24 ±5%	-	n.ph 1~
Supply Frequency	Hz	60		

WORKING DATA				
Air flow (acc. to ISO 1217 Annex C and Annex E for variable speed compressors)	l/min	3350		
	m ³ /min	3,35		
	c.f.m.	118,3		
Total Absorbed Power at full load (+ dryer)	kW	23,6	+	-
Total Absorbed Power at idle	kW	6,2		
Total Absorbed Current at full load (+ dryer)	A	30	+	-
Specific power absorption	kW/m ³ /min	6,60		
Max final air temperature above ambient	°C	12		
Removed Heat	kJ/h	75240		
Sound Pressure (acc. to Pneurop/Cagi PN2CPTC2)	dB(A)	72	± 3 dB(A)	

ELECTRIC MOTOR				
Nominal Motor Power	kW	22		
Size and Construction Form	-	160	-	IM B34
Synchronous Speed	min ⁻¹	3600		
Efficiency class and relative efficiency value	-	IE3	-	0,927
IP degree of protection and insulation class of the electric motor	-	IP 55	-	class F
Service factor	-	1,1		

VENTILATOR				
Type and number of installed fans	-	Radial	-	n. 2
Fan flow rate	m ³ /h	3300		
Nominal Power	kW	0,16		
IP degree of protection and insulation class of the fan	-	IP54	-	class F

LUBRICANT				
Type	-	RotarEcoFluid 46		
Oil quantity	l	7		
Oil carry over	mg/m ³	2-4		

SAFETY DEVICES				
Max oil working temperature	°C	110		
Pre-alarm oil working temperature	°C	105		
Safety valve setting	bar	14		
Protection type from electric motor overload	-	Thermal relay		

DIMENSIONS				
Length	mm	1510		
Width	mm	730		
Height	mm	1085		
Weight	kg	418		
Air outlet size	G	3/4"		
Drawing code	-	DIM0045		
Wiring diagram code	-	9017426		